



Antipodes EX Music Server



X-Series Modular Solutions

EX Music Server



The EX is our entry level product but is designed without any audio performance compromise, delivering a fast, detailed, natural and emotionally engaging presentation of your music. The EX also has a built-in good sounding analog output, avoiding the need to buy a DAC if you are coming to computer audio for the first time. You can upgrade by adding a high quality DAC and the EX will reveal its amazing potential. Or you can upgrade further by adding the CX, P1 or P2.

The EX has less processing power than our CX, but there are only a few Roon DSP features that are too demanding for it. You can easily play PCM files to up to 32bit/768kbps, and DSD to DSD512 with the EX. Upsampling to 32bit/768kbps PCM on-the-fly is also well within its capabilities. Only high intensity computations such as transcoding/upsampling to DSD256 and DSD512 on-the-fly are beyond its power limits.

Application Suite

Easy Point & Click Setup & Remote Control



Three Complete Playback Solutions



Three Renderer Applications



A Range Of Server Applications



We adopt an open systems approach to the applications installed on Antipodes Music Servers. This allows us to bring you the world's best file playback and streaming applications, as they emerge.

User Installable Storage



The EX can take up to two 2.5" 7mm SATA Drives, whether HDD or SSD, but SSD is highly recommended for superior sound. Installable by the owner or by the dealer.

Owners can purchase their storage and slide the drives in the rear slots, and then contact Antipodes Support to optimise the storage in a remote support session.

Upgrade Options



EX Standalone



EX & P1
- Isolation
- Auto-Ripper



EX & P2
- Isolation
- Re-Clocked Outputs



EX, P1 & P2
- Isolation
- Auto-Ripper
- Re-Clocked Outputs

CX+EX Solution



Specifications

Antipodes EX

Colour: Silver or Black

Storage Options:

User-Installable: Up to two 2.5" 7mm
Sata HDDs or SSDs

HARDWARE FEATURES

Medium Power V4X Circuit
Fanless All Alloy
Screened Chambers Construction
ODAPS2 Level 3 Internal Linear Power Supply
USB Audio 2.0 Output
PCM to 32bit / 768kHz PCM
DoP to DSD512, Native DSD to DSD512
Ethernet Direct Output
Stereo Analog Output

POWER

110-120VAC or 220-240VAC User-Switchable

DIMENSIONS & WEIGHT

240mm (w) x 290mm (d) x 90mm (h)
9.5in (w) x 11.4in (d) x 3.6in (h)
7.5kg or 16.5lbs

SOFTWARE FEATURES

Music Playback Options:

Room
SqueezeBox
MPD
DLNA/UPnP/OpenHome
HQPlayer
Spotify Connect
SONOS Integration
Plex Media Server

Admin Applications

Find My Antipodes
CD-Import Auto-Ripper
Playback App Switcher
External Drive Mounter
Browser-Based Setup GUI
SMB Server For File Management
& Downloads

WARRANTY

24 Months Return To Vendor Extendable
To 36 Months By Online Registration

More detailed information can be found on our website antipodesaudio.com



Antipodes Audio Limited
www.antipodesaudio.com
Manufactured In New Zealand

Copyright 2018 - All Rights Reserved